



**Specifications Ledvance LED  
Downlight Comfort High Efficiency U  
Aluminium White 15W 1950lm 55D -  
830 Warm White | 160mm - Cutout  
150mm**

[View Product](#)

## General Information

|                          |                                                                   |
|--------------------------|-------------------------------------------------------------------|
| SKU                      | 260217                                                            |
| EAN                      | 4099854686962                                                     |
| manufacturer_code        | 4099854686962                                                     |
| Brand                    | Ledvance                                                          |
| Manufacturer Name        | DOWNLIGHT COMFORT HIGH EFFICIENCY UGR<19 D150 P 15W ML 830 U19 WT |
| Any Lamp all-in warranty | 5 Years                                                           |
| Average Lifetime (h)     | 100000                                                            |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x18              |
| Wattage                     | 15W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 830 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 80-89             |

|                       |                                |
|-----------------------|--------------------------------|
| Colour of Light       | White                          |
| Light Colour Options  | Single Color                   |
| Beam Angle (degree)   | 55                             |
| Luminous Flux (Lumen) | 1950lm                         |
| Lumen per watt        | 130                            |
| Power factor          | >0.90                          |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | Opal                           |
| Product Type Category | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 150               |
| IP-Rating              | IP20              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 92  |
| Diameter (mm) | 160 |

## Sensor Information

## Why Any-lamp?

|                                                                                                                                                                                                                                                                   |           |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|
| Type of sensor                                                                                                                                                                                                                                                    | No Sensor |
|  Order from the <b>largest lighting specialist</b> in Europe  <b>Customised</b> quotation |           |
|  Up to <b>7 years warranty</b>  <b>Easy</b> return process                                  |           |